

Micro shutter controller module - Aeotec Nano Shutter

- Aeotec Nano Shutter micro shutter controller module
- Allows the motor controls of your shutter, awning, blind or blind to be connected to your Z-Wave network
- Command your blinds or shades remotely
- Installs behind an existing switch
- Up/down function (no positioning)
- Integrates the Z-Wave 500 series chip
- 250% faster communication compared to standard Z-Wave devices
- Supports Z-Wave S2 security framework
- Automatic switch type detection
- Compatible with all Z-Wave and Z-Wave+ controllers
- Instantaneous and cumulative consumption function measurement
- Use with toggle or impulse switches. Small, discreet, and aesthetic. Easy to use and install.

**Reference / Model****AEOTEC-009 / ZW141**

Module type: Z-Wave receiver

Compatible with all VESTA panels (Z-Wave)

Frequency: 868.42 Mhz

Transmission distance up to 150 metres in the open field

Wiring: 3 wires, neutral required

Maximum load: 2,5A

LED status indicator

Power supply: 120V ~ 240V AC, 50/60Hz

Standby power consumption: <0.8W

Operating temperature 0° ~ +40°C

Operating Humidity: 8% ~ 80%

Dimensions: 42.5 x 40 x 20 mm

Certifications: FCC, UL, CE, ROHS