

ACL580

Keypad, ABS plastic housing, standalone

Advanced keypads for access control and home automation

These standalone robust keypads are designed to operate in both indoor and outdoor environments. ACL580 keypads are available with backlit metallic/plastic keys and in a variety of plastic or metal housing options. These keypads offer elegant looks with a host of programmable options such as backlit keys, 1000 users, invalid code lockout, 2 pushbutton inputs, support for ACL870 push buttons, adjustable unlock timer etc. Can control two doors. Available in metal or plastic and surface or flush mounted.



Details

- Indoor/outdoor
- ABS housing with plastic keys
- Dust proof and water-resistant (IP65)
- Up to 1000 user codes
- Request To Exit using normal RTE button or ACL870 type pushbutton
- Codes can be 1 to 8 digit long
- Users can be assigned any of the available relays
- 30 second lockout after eight consecutive invalid PINs
- Red and green LED (relay status) and orange LED (Programming)

ACL580

Keypad, ABS plastic housing, standalone

Technical specifications

General

User interface	Touch-Tasten
Status-LEDs	3

Communication

Kommunikationsart	Verdrahtet
-------------------	------------

Inputs/Outputs

Eingänge	2
Eingabetyp	Request-To-Exit
Ausgänge	2
Ausgabetyyp	SPDT relays, Latch or pulsed mode (01 to 99 seconds)

Electrical

Betriebsspannung	12 / 24 VAC/VDC
Aktueller Verbrauch	150 mA max.

Physical

Abmessungen	84 x 108 x 40 mm
Form factor	Vertikal
Montage	Oberflächenmontage
Material	ABS

Environmental

Betriebstemperatur	-20 to +50°C
Relative Luftfeuchtigkeit	95% noncondensing
IP Klassifizierung	IP65

Regulatory

Kompatibilität	CE
Zertifizierung	CE



Als innovatives Unternehmen behält sich Carrier Fire & Security das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte de.firesecurityproducts.com online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.