



JA-156J Multifunctional panic button

The wireless multifunctional panic button is a device intended to enable the user to activate a panic alarm should the user find themselves in a situation requiring it. The device has multiple modes of activation, which must be configured via F-Link once the device has been enrolled onto the system.

TECHNICAL SPECIFICATION

Power	2 x Alkaline battery, type LR03 (AAA) 1.5 V/1.2 Ah
Typical battery lifetime	approx. 3 years
Maximum power consumption	40 mA
Compatibility	control panels JA-103K, JA-107K
Communication frequency	868.1 MHz, Jablotron protocol
Maximum radio-frequency output (ERP)	5 mW
Communication range	approx. 300 m
Classification	Security grade 2 / environmental class II, (EN 50131-1)
Environment	Indoor general
Ingress Protection Code	IP 22
Operational temperature range.	-10 °C to +40 °C
Dimensions (with mounting platform)	66 x 22 x 122 mm
Weight (w/o batteries)	88 g

4 TYPES OF USAGE




ALARM BUTTON
ACTIVATED BY HAND



ALARM BUTTON
ACTIVATED
BY FOOT OR KNEE



DETECTION OF
BANKNOTE OR VALUABLE
DOCUMENTS



VERIFICATION OF
THE PRESENCE
OF A PERSON
(variable timer)