



KEY FEATURES

- IP monitor for indoors with 0,3MP camera
- 7" capacitive touchscreen (1024x600). Touch keys
- Panic call
- Built in microphone and speaker
- Fast Ethernet
- Alarm: 2 in / 2 out
- 12V DC
- PonC

FEATURES

- IP monitor for indoors with 7" capacitive touchscreen
- Resolution: 1024 x 600
- Capacitive touch keys
- 0,3 Mpx IP cameras
- H.264
- Linux O/S
- Hands-free audiovisual communication with the door station and the master station in the intercom system
- Panic call
- G.711u
- Built in speaker and microphone (omnidirectional)
- Supports monitoring door stations and external cameras
- Remote unlocking via the client software or app
- High-performance embedded SOC processor
- 8-ch zone alarm supported
- Alarm messages to the master station, to the client software or to the app once the alarm sensor is activated
- Message notification function (including written messages and voice messages)
- Community notice supported
- Alarm: 2 in / 2 out
- MicroSD card slot up to 32GB (card is not included)
- RS485 Half-Duplex
- Ethernet 10/100Mbps auto-adaptive
- Network protocol: TCP/IP y RTSP
- Power supply 12V CC / PonC (requires HYU-560)
- Working temperature: -10°C ~ +55°C
- Working RH 10% ~ 90%
- For indoors
- Dimensions: 217 x 142 x 26 mm

RELATED PRODUCTS



HYU-558

HYU-557

HYU-560