

# HYU-412N

SF-IPT855ZW-4E

HYUNDAI

## IP dome with IR illumination of 20~30m, for outdoors 4 MP

HYUNDAI  PerformanceLine  P2P 

- IP dome with IR illumination of 20~30m, for outdoors 4 MP
- H.265+/H.265/H.264/H.264+/MJPEG
- 1/3" CMOS, 4MP
- Digital resolution 4MP, 1080P, 720P, 20FPS
- Mechanical filter
- 0,01 lux
- 2,8~12 mm (98°~30°) motorized lens with autofocus
- OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI
- IP67, IK10
- 3AXIS
- 12V DC
- PoE.



### Reference / Model

HYU-412N / SF-IPT855ZW-4E

1/3" CMOS sensor, 4 MP

Digital resolution: 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720),etc.

H.265+/H.265/H.264+/H.264/MJPEG

Stream 1: 4MP, 1080P, 720P (20 fps)

Stream 2: D1, CIF, VGA, QVGA (20 fps)

Day/night mode with removable mechanical filter

IR illumination: 20~30meters

Minimum illumination: 0,01 lux F1.2 color / 0,018 lux F1.6 color / 0 lux IR On

2,8 ~ 12 mm (98°~30°) motorized lens with autofocus

OSD menu,AGC, BLC, real WDR 120dB, 3D-DNR

1fixed ROI stream 1 and stream2

Motion detection and privacy mask

Adjustment: brightness, saturation, contrast, sharpness, mirror

**IP dome with IR illumination of 20~30m, for outdoors 4 MP****Reference / Model****HYU-412N / SF-IPT855ZW-4E**

Network interface: RJ45 (10/100 Base-T)

Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6 UDP, Bonjour

Compatible with ONVIF (Profile S, G), ISAPI

Plug&amp;Play with NVR NEXTGEN

Compatible with DDNS DEMES

Power supply: 12V DC /11W (PoE 12,9W)

PoE 802.3af

Working temperature -30°C ~ +60°C

RH: 95% (without condensation)

IP67

IK10

Lightning-proof 2KV

Metal case

Dimensions: Ø130,5x 102,4mm

Weight: 485g

3AXIS: wall and ceiling installation

Power supply is not included