



## KEY FEATURES

- 22" LED monitor
- 16:9
- Native resolution 1920 x 1080
- 1 HDMI, 1 BNC, 1 VGA
- 1x BNC output
- Allows direct connection supported of CVI/TVI/AHD cameras in the HD BNC input till 5.0MP
- Operation 24x7
- MTBF 50.000 hours

## 22" LED MONITOR . 16:9

- 22" LED monitor
- 16:9 aspect ratio
- PAL, NTSC and SECAM with automatic detection
- Native resolution: 1920x1080
- Brightness: 350 cd/m<sup>2</sup>
- 1000:1 contrast
- Color depth: 24 bits (16,7 million colors)
- Pixel size: 0,248 x 0,248
- Viewing angle: 178°/178° (horizontal/vertical)
- Response time: 5 ms
- High fidelity digital processin, bright and vivid video
- 3D digital noise reduction technology
- 3D digital filter
- OSD control: automatic adjustment, brightness, contrast, horizontal/vertical position, clock, fase, color, language, etc.
- Input interface: 1 HDMI (2.0), 1 BNC, 1 VGA
- Allows direct connection from CVI/TVI/AHD cameras in the HD BNC input till 5.0MP
- HDCVI: 4MP/1080P cameras, up to 500 meters
- HDTVI: 5MP/4MP cameras, up to 300 meters
- AHD: 5MP/4MP cameras, up to 500 meters
- Output interface: 1 BNC
- Extended working temperature: -30°C ~ +85°C
- Power supply: 12V ~ 24V DC, 50/60Hz
- Consumption: ≤20W
- VESA mount
- Dimensions: 476,64 (wide) x 268,11 (height) mm
- 24x7
- MTBF: 50.000 hours