

FIXED IP DOME WITH IR ILLUMINATION OF 40 M, FOR OUTDOORS



H.265 ONVIF

## KEY FEATURES

- Fixed IP dome with IR illumination of 40 m, for outdoors
- H.265/MJPEG
- 1/2,5" Sony® Starvis CMOS, 8 MP
- 8MP @25/30 fps
- Dual stream
- 3,6 ~ 12 mm autofocus motorized lens
- ICR filter
- OSD, WDR, 3D-DNR, motion detection and privacy masks
- Audio: 1 in / 1 out
- Onvif

- 1/2,5 Sony® Starvis CMOS sensor, 8 MP
- Digital resolution: 8MP (3840x2160), 5MP (2592x1944), 4MP (2592x1520), 3MP (2048x1520), 1,3MP (1280x1080), 720P (1280x720), D1 (720x576), VGA (640x480), EGA (640x352), QVGA (320x240)
- H.265/MJPEG
- Stream 1: 8MP, 5MP, 720P (1~25 fps)
- Stream 2: D1, VGA, (1~25 fps)
- Removable mechanical filter
- SmartIR: 3led array, 40meters
- Minimum illumination: 0,01 lux F1.2 (color) / 0 lux IR ON
- 3,6 ~ 12 mm autofocus motorized lens
- OSD menu, WDR, 3D-DNR
- Motion detection and privacy mask
- Audio: 1 in / 1 out
- Integration with other brands by Onvif 2.4, SDK y RTSP
- Compatible with ZVR/NVR NEXTGEN via Onvif
- P2P intuitive by QR code
- Free Webserver and CMS
- Power supply in/out: 12V (to power external microphone)
- PoE supported
- Working temperature: -20°C ~ +60°C
- IP66
- PVC and metal case
- Dimensions: Ø126,6 x 110,8mm
- 3AXIS: wall and ceiling installation
- Reset button
- Waterproof cable

## RELATED PRODUCTS

