

4 CHANNEL 5 IN 1 ZVR HDCVI/HDTVI/AHD/CVBS + 1 IP CHANNELS

## KEY FEATURES

- 4 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 1 IP channels
- H.265+/H265/H.264+/H264
- 2 way audio
- 4 channel playback 1080P
- Recording 4 MP (1 IP input) 4M-N, 3MP (channel 1, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF (25 fps)
- HDMI and VGA at 1080P
- 1 HDD SATA capacity
- Onvif, P2P, DDNS
- 2 USB
- 12V DC



**H.265+ P2P Onvif HDCVI™**  
**HDTVI AHD CVBS**

## RELATED PRODUCTS



HYU-383-1TB



- 4 channel 5 in 1 ZVR, H.265+/H265/H.264+/H.264
  - 5 technologies: IP, HDCVI, HDTV, AHD and CVBS
  - H.265+ compression format (reduction of 70% coding efficiency and video storage)
  - 4 BNC input (coaxitron supported):
  - HDCVI: 1080P/720P (telemetry control via HDCVI coaxial cable)
  - HDTV: 4MN / 3MP / 1080P / 720P (only on v3.0 cameras, not compatible with v1.0)
  - AHD: 1080P/720P
  - CVBS : 960H
  - 1 IP inputs up to 4MP
  - HDMI & VGA output 1920x1080
  - BNC auxiliary output up to 704x576
  - 2 way audio: 1 RCA in / 1 RCA out
  - Display resolution: 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF
  - Recording resolution: 3MP (channels 1, only TVI), 4MP (only IP), 1080P, 1080N (960x1080), 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF
  - Stream 1 on 3MP mode:
  - Stream at 4MN/3MP: 4M-N, 3MP (15 fps)
  - Stream 1 on 1080P mode:
  - Stream at 1080P: 1080P, 720P (15 fps), 960H, D1/4CIF, VGA, CIF (25/30 fps)
  - Stream at 720P: 720P, 960H, D1/4CIF, VGA, CIF (25/30 fps)
  - Stream 2: 960H, D1/4CIF (12 fps), CIF (25/30 fps)
  - 4 channel simultaneous playback 1080P
  - Multi-camera inverted playback
  - Up to x256 playback speed (forward and backward)
  - 1 HDD SATA up to 4TB (not included)
  - Soporta modo de cuota de disco duro; permite asignar capacidades diferentes a canales diferentes
  - GUI and one touch recording (Wizard)
  - Diagnosys manual of video quality
  - Search and playback by tags
  - Log files locking and unlocking
  - Network interface: Ethernet RJ45 (10/100M) auto-adaptive
  - Network protocols: TCP/IP, PPPoE, DHCP, P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS
  - Compatible with ONVIF
  - Remote access up to 128 users
  - Remote access via iPhone/iPad, Android
  - Multi browser compatibility: Chrome, Firefox, Safari, IE
  - P2P, DDNS DEMES, Push and zero channel
  - Connection: 2 USB 2.0
  - Power supply: 12V DC
  - Consumption: ≤8W
  - Working temperature: -10°C ~ +55°C
  - RH: 10~90%
  - Dimensions: 200 x 200 x 45 mm (desktop)
- Weight: ≤1 kg