



PerformanceLine ~~IP67~~ **P2P**



KEY FEATURES

- IP vandal dome with IR illumination of 30m, for outdoors, 4 MP
- H.265+/H.265/H.264/H.264+/MJPEG
- 1/3" CMOS, 4MP
- Digital resolution: 4MP, 1080P, 720P, 20FPS
- Mechanical filter
- 0,01 lux
- 2,8 mm fixed lens (100°)
- OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI
- IP67, IK10
- 2AXIS

IP VANDAL DOME WITH IR ILLUMINATION OF 30M, FOR OUTDOORS, 4 MP

- 1/3" CMOS sensor, 4 MP- Digital resolution: 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720), etc.- H.265+/H.265/H.264+/H.264/MJPEG- Stream 1: 4MP, 1080P, 720P (20 fps)- Stream 2: D1, CIF, VGA, QVGA (20 fps)- Day/night mode with removable mechanical filter- IR illumination: 30 meters- Minimum illumination: 0,01 lux F1.2 color / 0,028 lux F2.0 color / 0 lux IR On- 2,8 mm fixed lens (100°)- OSD menu, AGC, BLC, digital WDR, 3D-DNR- 1 fixed ROI stream 1 and stream 2- Motion detection and privacy mask- Bright adjustment, saturation, contrast, sharpness, mirror- Network interface: RJ45 (10/100 Base-T) - Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6 UDP, Bonjour- Compatible with ONVIF (Profile S, G), ISAPI- Plug&Play with NVR NEXTGEN- Compatible with DDNS DEMES- Power supply: 12V DC /5W (Max 7W PoE)- PoE 802.3af supported- Working temperature: -30°C ~ +50°C- RH: 95%- IP67- IK10- Lightning-proof 2KV- Metal case- Dimensions: Ø111 x 82,4 mm- Weight: 410 g- 2AXIS: 0°~355°(PAN), 0°~70°(TILT)
- Reset button- Power supply is not included