

IP BULLET PTZ WITH IR ILLUMINATION OF 30~40 M FOR OUTDOORS



IP65 5MP P2P Onvif

KEY FEATURES

- IP bullet PTZ with IR illumination of 30~40 m for outdoors
- 1/2,9 Sony® CMOS, 6,8 MP
- H.265/H.264
- 5MP@18 fps, 4MP@25 fps, 3MP/1080P/720P@30 fps
- 4X optical zoom (2,7~13,5 mm)
- ICR
- OSD, AWB, AGC, BLC, digital WDR, 2D/3D-DNR, mirror, motion detection and privacy mask
- 180° positioner
- 1 preset
- IP65, Lightning-proof 4KV

FEATURES

- 1/2,9" Sony® CMOS, 6,8 MP
- H.265 / H.264
- Digital resolution: 5MP (2592x1944), 4MP (2592x1520), 3MP, 1080P (1920x1080), 720P (1280x720), etc.
- Stream 1: 5MP (18 fps), 4MP (25 fps), 3MP/1080P/720P (30 fps)
- Stream 2: VGA/360P (30 fps)
- Removable mechanical filter
- IR illumination: 6 SMD led, 30 ~ 40 meters
- Minimum illumination: 0,1 lux F1.2 (color, AGC On) / 0 lux IR On
- 4X optical zoom (2,7 ~ 13,5 mm)
- OSD menu
- Auto white balance
- Auto gain control
- BLC, digital WDR
- 2D/3D-DNR
- Mirror mode
- Motion detection and privacy mask
- Positioner: 0°~180° (H), 0°~55° (V)
- Manual speed: 0,5° ~ 20°/sec. horizontal / 0,5° ~ 10°/sec. vertical
- 1 preset point
- Guard position
- Shutdown recovery
- 1x RJ45 100Mbps
- Network protocols: HTTP, RTSP, FTP, NFS, SMTP, DHCP, NTP, etc.
- Compatible with Onvif (2.6) y RTSP
- Power supply: 12V DC (±10%), <10W
- Working temperature: -20°C ~ +60°C
- RH: 10%~90%
- IP65
- Lightning-proof 4KV
- Dimensions: Ø68 x 91 mm

RELATED PRODUCTS



HYU-543