



KEY FEATURES

- IP fisheye vandal dome with IR of 15m, for outdoors
- H.264/MJPEG
- Digital resolution: 12MP (4000x3072), etc
- 1,98 mm fisheye lens, 360°
- OSD, AGC, BLC, digital WDR, 3D-DNR, 4 ROI
- IVS
- MicroSD/SDHC/SDXC
- IP66, IK10
- 12V DC
- PoE

FEATURES

- 1/1,7" CMOS sensor, 12,4
- Digital resolution: 4000x3072, 3072x3072, 3072x2304, 2560x2560, 2048x2048, 3072x1152, 1600x1200, 1280x1280, 720x720, 704x576
- H.264/MJPEG
- Display mode 1: 1 fisheye (stream principal) + 1 fisheye (stream secundario) + 3 PTZ
- Display mode 2: 1 panorámica (stream principal) + 1 panorámica (stream secundario)
- Display mode 3: 4 PTZ
- Display mode 4: fisheye
- Coding mode 1 : 1 fisheye (2560x2560/2048x2048/1280x1280, 10 fps) + 1 fisheye (720x720, 10 fps) + 3 PTZ (1600x1200, 10 fps)
- Coding mode 2: 1 panoramic (3072x2304/3072x1152, 12 fps) + 1 panoramic (704x576, 12 fps) + 3 PTZ (1600x1200, 10 fps)
- Coding mode 3: 4 PTZ (1600x1200, 12 fps)
- Coding mode 4: 1 fisheye (4000x3072, 20 fps; 3072x3072/2560x2560, 25 fps) + 1 fisheye (720x720/704x576, 12 fps)
- Day/night mode with removable mechanical filter
- IR illumination: 15 meters
- Minimum illumination: 0,01 lux F1.2 color / 0,04 lux F2.4 color / 0 lux IR On
- 1,98 mm fisheye lens (360°)
- OSD menu
- White balance
- Automatic gain control
- BLC, digital WDR
- 3D-DNR
- 4x fixed ROI per stream
- Brightness, saturation, contrast, sharpness, tone
- Smart functions: Line crossing detection, intrusion detection, heat map (records the movement of pedestrian traffic over a period of time and shows the temporal density and spatial statistics in different colors), counting people
- Built in microphone and speaker
- MicroSD/SDHC/SDXC (up to 128 GB)
- Network interface: RJ45 (10/100/1000M)
- Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP
- Compatible with ONVIF (Profile S, G), PSIA, CGI, ISAPI
- Plug&Play with NVR NEXTGEN
- Compatible with DDNS DEMES
- Power supply: 12V DC (±10%)
- Max consumption: 14,7W

RELATED PRODUCTS

