

HD-TVI DOME PRO SERIES WITH SMART IR OF 60 M, VANDAL PROTECTION FOR OUTDOORS



KEY FEATURES

- HD-TVI dome PRO series with Smart IR of 60 m, vandal protection for outdoors
- 2MP CMOS
- HD-TVI video output
- 2,7~13,5 mm motorlens with autofocus (103°~32,1°)
- ICR filter
- OSD, AWB, AGC, BLC, HLC, WDR 130dB, 3D-DNR, image adjustment, motion detection and privacy mask
- IP67, IK10
- 3AXIS
- 12V DC
- PoC.af compatible

FEATURES

- 2 MP, 1920x1080
- Ultralow illumination
- WDR true 130dB, 3DDNR
- 2,7 ~ 13,5 mm motor lens with autofocus
- Smart IR with 60 meter range
- Power supply over coaxial cable
- IP67, IK10

SPECS

- CMOS sensor, 2 MP
- Digital resolution: 1080P (1920x1080) at 25 fps
- HDTV I video output
- 0,003 lux F1.2 (color, AGC On) / 0 lux IR On
- Removable mechanical filter
- Smart IR: 60 meters
- 2,7 ~ 13,5 mm motor lens with autofocus
- Horizontal viewing angle: 103°~32,1°
- OSD via coaxial (300 m range)
- Auto/manual white balance
- Automatic gain control
- Backlight compensation: BLC, HLC
- WDR true 130dB
- 3DDNR
- Mirror mode supported
- Adjustment of brightness and sharpness
- Motion detection: 4 programmable zones
- Privacy mask: 4 programmable zones
- Working temperature: 40°C~+60°C
- RH 90% (without condensation)
- IP67
- IK10
- Metal case
- Power supply: 12V DC (±25%)
- Consumption: 7W
- PoC.af supported (power supply over coaxial) que funciona especialmente con ZVR PoC
- Dimensions: Ø145 x 111,3 mm
- Weight: 890 g
- 3AXIS: 0°~340°(PAN), 0°~75°(TILT), 0°~355°(Rotation)