

32 CH NYUNDAI NEXTGEN IP NVR . H264 +

**KEY FEATURES**

- 32 ch NYUNDAI NEXTGEN IP NVR
- H.264 +
- Synchronous playback of up to 16 channels
- Display up to 6MP
- Recording 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc
- Recording of up to 160 Mbps
- HDMI and VGA outputs at 1080P
- Bidirectional audio
- 4 inputs / 1 alarm output
- Supports 2 SATA HDD

**FEATURES**

- 32channel HYUNDAI NEXTGEN IP NVR format H.264 +
- The H.264 + compression format improves encoding efficiency by up to 50% and reduces the costs of storing video data
- Export to AVI format
- 32 IP camera inputs
- Incoming bandwidth: 160 Mbps
- Outgoing Bandwidth: 80 Mbps
- HDMI and VGA 1080P video outputs
- Bidirectional audio: 1 RCA input / 1 RCA output
- Recording resolution: 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, etc.
- Live display up to 6MP
- Allows instant playback of assigned channel during multichannel display mode
- Simultaneous playback of 16 D1 / 4CIF channels, 12 720P channels, 6 1080P channels
- Alarm channels: 4 inputs / 1 output
- Supports multiple VCA (Video Content Analytics) events
- Smart record search
- Storage: 2 SATA ports for up to 2 HDD with max. 4TB per disk (HDD not included)
- 1 RJ45 (10/100 / 1000M) autoadaptive ports
- Protocols: TCP / IP, DHCP, P2P, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS
- ONVIF compatible
- Remote access for up to 128 users
- Remote access through iPhone / iPad devices, Android
- Multi browser compatibility: Chrome, Firefox, Safari, IE
- P2P in the cloud, DDNS DEMES, Push and zero channel
- Plug & Play connection with NEXTGEN IP cameras
- Connections: 1 USB 2.0, 1 USB 3.0
- Power: 12V DC
- NVR consumption: ≤10W (without hard drives)
- Operating temperature: 10 °C ~ + 55 °C
- Relative humidity: 10 ~ 90%
- Dimensions: 385 x 315 x 52 mm (1U)
- Weight: ≤1 kg