



**KEY FEATURES**

- AirSpace IP dome with Smart IR 30 m for outdoor
- H.265 / H.264 / MJPEG format
- 1/2.8" Sony® Starvis CMOS, 2 MP
- 1080P @ 20 fps
- Dual Stream 3.6 mm lens
- ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks
- Audio: 1 in / 1 out
- Onvif
- IP67 12V DC PoE Reset button

**HYU-749** HYU-749

AIRSPACE IP DOME WITH SMART IR 30 M FOR OUTDOOR

**FEATURES**

- 1/2.8" Sony® Starvis CMOS, 2 MP
- H.265 and H.264 encoding with dual stream
- Resolution 1080P (1920x1080) at 20 fps
- Digital WDR, day / night with ICR filter, 2D / 3DDNR, AWB, AGC, 4 ROI
- 3.6 mm lens
- Smart IR up to 30 meters
- IP67
- Supports PoE

**SPECS**

- 1 / 2.8 Sony® Starvis 2 megapixel CMOS sensor
- H.265 / H.264 / MJPEG compression formats
- Dual stream
- Digital resolution: 1080P (1920x1080), 1.4MP (1920x720), D1 (720x576), VGA (640x480)
- Stream 1: 1080P (20 fps), 1.4MP (25 fps)
- Stream 2: D1, VGA, (25 fps)
- Supports constant and variable bit rate (CBR / VBR)
- Day / night mode with removable mechanical filter
- Smart IR: 24 SMD LEDs, 30 meters
- 0.001 lux (color) / 0 lux IR ON
- 3.6 mm lens
- OSD overlay
- Auto white balance
- Automatic gain control
- Automatic exposure control
- Digital WDR
- 2D / 3DDNR digital noise reduction
- 4 ROI zones
- Motion detection and privacy mask
- Adjust brightness, contrast, saturation, sharpness and image rotation (normal, 90 °, 270 ° and automatic)
- Intelligent detection: Occlusion detection, blur detection, brightness detection, color detection, sound detection, abandon detection, motion detection, virtual cord, regional invasion
- Audio: 1 input / 1 output
- Network interface: RJ45 (10 / 100M) autoadaptable
- Network protocols: IPv4, IPv6, HTTP, HTTPS, 802.1x, TCP / IP, UDP, RTP, RTCP, UPNP, RTSP, SMTP, NTP,
- DHCP, DNS, PPPOE, DDNS, FTP
- Onvif compatible
- Supports cloud service
- Compatible with iOS and Android devices