



PerformanceLine H265 P2P

Onvif 4MP

KEY FEATURES

- HYUNDAI IP dome with IR of 30m , 4MP for outdoors
- H.265 / H.264 / MJPEG format
- 1/3" CMOS, 4MP
- Digital resolution of 4MP, 1080P, 720P, 20FPS
- Mechanical filter
- 0.018 lux
- 2.8 ~ 12 mm (98 ° ~ 28 °) motor lens with autofocus
- OSD, AGC, BLC, WDR true 120dB, 3D-DNR, motion detection, privacy masks, fixed ROI zone, MicroSD / SDHC / SDXC slot, IP67, IK10, 3AXIS, 12V DC, PoE

HYU-767 HYU-767

HYUNDAI IP DOME WITH IR OF 30M , 4MP FOR OUTDOORS

FEATURES

- 1/3" CMOS sensor 4 MP
- Digital resolution: 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 720P (1280x720), etc.
- H.265 / H.264 / MJPEG compression format
- Main Stream: 4MP, 3MP, 1080P, 720P (20 fps)
- Secondary stream: 640x480, 640x360, 320x240 (20 fps)
- Day / night mode with removable mechanical filter
- Infrared lighting: 30 meters
- 0.018 lux F1.6 color / 0 lux IR On
- 2.8 ~ 12mm motorized lens with autofocus
- Viewing angle: 98 ° ~ 28 ° (H), 51 ° ~ 16 ° (V), 115 ° ~ 32 ° (D)
- OSD menu
- Automatic gain control
- White balance adjustable from client software or web browser
- Backlight Compensation: BLC
- Real WDR 120dB
- 3D digital noise reduction
- 1 fixed ROI zone main stream and secondary stream
- Motion detection and privacy mask
- Brightness adjustment, saturation, contrast, sharpness
- MicroSD / SDHC / SDXC card slot (up to 128 GB)
- Network interface: RJ45 (10 / 100M) autoadaptive
- Network protocols: TCP / IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP,
- UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6 UDP, Bonjour
- Compatible with ONVIF (Profile S, G), ISAPI
- Plug & Play connection with NVR NEXTGEN
- DDNS DEMES compatible
- Compatible with IE8 +, Chrome 31.044, Firefox 30.0-51, Safari 8.0+ browsers
- Power supply: 12V DC (\pm 25%)
- Consumption: 10W (12W PoE)
- Supports 802.3af PoE, class 3
- Operating temperature of 30 ° C ~ + 50 ° C
- Humidity: 95% (no condensation)
- IP67
- IK10
- Lightningproof 2KV
- Metal and plastic case
- Dimensions: Ø141 x 99.9 mm
- Weight: 820 g
- 3AXIS: 0 ° ~ 355 ° (PAN), 0 ° ~ 70 ° (TILT), 0 ° ~ 360 ° (Rotation)
- Power supply is not included