

## Model: VIS-ISMART504





		Specs
	Sensor	1/3" CMOS
Camera	Focal Length	3.6 mm
	Aperture	F2.0
	Optical Field of View	100° diagonal, 85° horizontal, 48° vertical
	Minimum Illumination	0.01 lux
Audio	Input	Built-in microphone
	Output	Built-in speaker
	Two-way Audio	Full duplex
	Audio Compressing	AAC
Video	Video Compressing	H.264, H.265
	Lighting Frequency	50 Hz, 60 Hz
	Frame Rate	15 fps
	Maximum Resolution	1920 x 1080
	Light Source For Night Vision	Infrared LED switchable
Network	Wireless Standard	2.4 GHz Wi-Fi (IEEE 802.11 b/g/n)
	Protocols Supported	TCP/IP, UDP/IP, DHCP, RTMP, MUTP
	IP Address Type	Dynamic IP address
Recording	Recording Method	Alarm triggered recording, and manual recording
	Video Storage	Cloud storage, local Micro SD card (up to 128 GB), and mobile phone memory
Function	Al Function	Human detection, vehicle detection, pet snap, motion tracking
	Wake-up Method	PIR body induction wake-up and remote wake-up
	Alarm Notification	Alarm push by mobile app, white LED flashing and alarm sound warning
	Rotation Angle	0° ~ 355° pan, -30° ~ 90° tilt
	Indicator	RGB tri-color LED
	Power	Micro USB
Interface	Storage	Micro SD card
	Key	Reset key
	Installation Method	Wall mount, ceiling mount, desktop
Installation	Bracket Type	1/4" universal screw hole
Environment	Dustproof and Waterproof	N/A
	Operating Temperature	-10 °C ~ 45 °C
	Storage Temperature	-20 ℃ ~ 60 ℃
	Dimension	70 mm × 85 mm × 105 mm (without bracket)
Prodoct Dimension	Bare Weight	185 g
	Finished Weight	700 g
	Material	ABS+PC
	Color	Black, white, grey, yellow, purple, pink optional
Certification	Certification	CE, FCC





