

# AS620RF-TR-N

## Spare transceiver unit for AS620RF-N, 868 Mhz

---

The AS620RF-TR-N is a spare transceiver module with housing and compatible with the AS620RF-N wireless siren. The unit is intended for indoor installation. The transceiver is able to control up to 4 wireless sirens and to receive and manage all information coming from the memorized sirens.

The transceiver features inputs and outputs to interface with an alarm control panel, along with buttons, LEDs, and a display for programming and fault indication.

Optionally, up to 4 remote controls can be added to allow the end-user to operate additional outputs through his security system in a quick and easy way.



### Einzelheiten

---

- Spare transceiver for AS620-RF-N
- Two-way wireless communication
- Plastic housing with tamper protection
- In- and outputs to be used in conjunction with any alarm control panel
- Two 7-segment displays for fault indication and programming

# AS620RF-TR-N

Spare transceiver unit for AS620RF-N, 868 Mhz

## Technische Spezifikationen

---

### Elektrische Angaben

---

Betriebsspannung	12 VDC
Aktueller Verbrauch	50 mA (maximum) 10 mA (nominal)

---

### Physikalisch

---

Abmessungen	155 x 100 x 50 mm
Liefergewicht	165 g

---

### Umweltbedingungen

---

Betriebstemperatur	-10 to +50°C
--------------------	--------------

---

### General

---

Operating frequency	868 MHz
Maximum power output	10 mW
Wireless signal range	500 m
Compatability	AS620RF-N, AS620RF-RC

---



Als innovatives Unternehmen behält sich Kidde Global Solutions das Recht vor, Produktspezifikationen ohne Ankündigungen zu ändern. Für die aktuellsten Produktspezifikationen, besuchen Sie bitte [de.firesecurityproducts.com](http://de.firesecurityproducts.com) online oder kontaktieren Sie bitte unsere Vertriebsmitarbeiter.